

The Implements of trailed and mounting types of disc harrows are mounted to the tractors by three point linkages. Additionally, the user can also use it as trailed type. Disc harrows are made of steel square rods arranged in row with bearings. High resistant, heat treated disc set frames are connected main frame. Used for scrapping pieces on the soil and stems of sunflower, wheat, rice, plant remnants wild grass. And also to break the surface of the soil and mix the manure and chemical fertilizers with the soil. Disc harrows are used either in cultivating vineyard, garden, fruit tree and olive tree fields or in cultivating plain fields. Preferably used type in the fields of trees and vineyards is mounted type and in the plain fields, the trailed type is preferred.



TECNICAL SPECIFICATIONS

Units		CRP2	CRP3	CRP4	CRP5	CRP6
Number of Bodies	pcs	2	3	4	5	6
Total Length	cm	193	284	378	450	600
Total Width	cm	170	204	238	285	320
Total Height	cm	158	158	158	164	164
Working Depth	cm	35	35	35	35	35
Working Width	cm	62-90	93-135	120-180	155-225	180-252
Space of Body	cm	85	80	80	85	80
Body Size	inch	14	14	14	14	14
Chassis Size	mm	140X120	140X120	140X120	160X120	160X140
Tractor Power	hp	60-65	80-85	90-120	130-60	170-195
Total Weightkg	550	890	1065	1305	1540	

